**Project title:** Reference: **Quantity:** Price:



## **MIRA 100**


## **Adjustable In-Ground IP Rated Uplighter**


The MIRA 100 is a powerful in-ground uplighter The MIRA 100 is preferred to the MIRA 38 for larger vegetation such as trees and bushes. Its adjustable uplight capabilities make it ideal for wall washing in outdoor areas.











Luminaire Data	Standard	Special Order
Power	4W	
Luminous Flux	462 Lumens	
Light Source	OSRAM OSLON SSL	
Colour Rendition Index (CRI)	90	
Colour Temperature	2700K	
Beam Angle	13°	
Ingress Protection Rating (IP)	IP67	
Dimmable	No	
Driver	External 24V 7W Drive	er
Directional	Yes	
Dimensions		
Size	Ø 97 x 60mm	
Cut Out Size	161 x 170 x H128mm (mounting box dimensions)	
Minimum Floor Depth	128mm	
General Data		
Colour options	Stainless Steel	
Warranty	5 year	
	1	

www.pleolight.com

ROI Office No. (+353) 1 293 6800 ROI Mobile No. (+353) 87 255 4334 UK Offfice No. +44 7387 272330

Technical data on this document is guidance only and is subject to change without prior notice. Measurements included on document are not exact and products sizes may differ slightly





